

# 熱軋 產品可接單規格表

Available Specification for Hot Rolled Product

單位 Unit:mm

訂單厚度 Order Thickness	訂單寬度 Order Width	900~986	987~1181	1182~1381	1381~1547
產品特性及鋼種 Steel Grade					
300 N/mm <sup>2</sup> 一般品級 Commercial Quality	ASTM A569 JIS G3131 SPHC JIS G3131 SPHD JIS G3132 SPHT1 SAE 1006 SAE 1008	1.20~12.70	1.20~12.70	1.20~12.70	1.80~12.70
300 N/mm <sup>2</sup> 沖軋品級 Drawing Quality	CH 1002	1.60~12.70	1.60~12.70	1.60~12.70	—
300 N/mm <sup>2</sup> 極低碳鋼 Extra Low Carbon Steel	CH M1005	1.71~12.70	1.71~12.70	1.71~12.70	—
350 N/mm <sup>2</sup>	ASTM A570 Gr.33 JIS G3132 SPHT2 SAE 1010 SAE 1012	1.35~12.70	1.35~12.70	1.45~12.70	—
400 N/mm <sup>2</sup>	API 5L Gr. B API 5L X42 ASTM A36 ASTM A570 Gr.36 ASTM A570 Gr.40 JIS G3132 SPHT3 JIS G3101 SS400 SAE 1017	1.50~12.70	1.50~12.70	1.50~12.70	2.00~12.70
450/500 N/mm <sup>2</sup>	ASTM A570 Gr.45 ASTM A570 Gr.50 ASTM A570 Gr.55 BS 4360 Gr. 43A BS 4360 Gr. 50B JIS G3101 SS490 SAE 1020 SAE 1022	1.40~12.70	1.40~12.70	1.40~12.70	—
450/500 N/mm <sup>2</sup> 高強度低合金鋼 High Strength Low Alloy	API 5CT J55 API 5L X52 ASTM A607 Gr.45 ASTM A607 Gr.50 ASTM A607 Gr.55	1.60~12.70	1.60~12.70	1.60~12.70	5.50~6.39
500 N/mm <sup>2</sup> 耐候鋼 Corten	JIS G3125 SPA-H	1.50~12.70	1.50~12.70	1.50~12.70	—

備註 Remark:

1. A1011 CS為2000年取代原A569。
2. A1011 SS為2000年取代原A570。
3. A1011 HSLAS 為2000年取代原A607。

# 熱軋 產品可接單規格表

Available Specification for Hot Rolled Product

單位 Unit:mm

Order Thickness		Order Width	900~986	987~1181	1182~1381	1381~1547
產品特性及鋼種 Steel Grade						
600 N/mm <sup>2</sup> 高強度低合金鋼 High Strength Low Alloy	API 5L X60		6.40~9.09	6.40~9.09	6.40~9.09	—
600 N/mm <sup>2</sup> 中碳鋼 Medium Carbon	SAE 1035 SAE 1050		1.45~12.70	2.00~12.70	—	—
300 N/mm <sup>2</sup> 花紋鋼捲 Checked Plate	CH FPC		2.00~12.70	2.00~12.70	2.00~12.70	2.76~12.70
400 N/mm <sup>2</sup> 花紋鋼捲 Checked Plate	CH FPSS		2.30~9.09	2.30~9.09	2.30~9.09	2.76~6.39

# 熱軋 產品品質保證範圍

Quality Guarante for Hot Rolled Product

單位 Unit:mm

Item	Hot rolled coil, non-skinpass	Hot rolled coil, skinpass
厚度公差 Tolerance on thickness	參照JIS、ASTM公差 As per ASTM and JIS standards	
寬度公差 Tolerance on Width	-0, +25mm 參照各規範	
機械性質 Mechanical property	As per ASTM, JIS or others standard 參照各規範	
化學成份 Chemical composition	As per ASTM, JIS and others standards	
單重 Coil weight	3' : 12~18 噸	3' : 6~10或12~18 噸
	3.5' : 15~19.5 噸	3.5' : 6~11或15~19.5 噸
	4' : 16~22 噸	4' : 8~13或16~22 噸
	5' : 16~23 噸	5' : 8~14或16~23 噸
	3' : 12~18tons	3' : 6~10 or 12~18 tons
	3.5' : 15~19.5 tons	3.5' : 6~11 or 15~19.5 tons
	4' : 16~22 tons	4' : 8~13 or 16~22 tons
	5' : 16~23 tons	5' : 8~14 or 16~23 tons
內徑 Inside diameter	762±35mm	762±25mm